

DATA SHEET 18334.115.43000

Folarex HXF

This highly heat stabilised copying drawing film, anti static on both sides, has a matt coating and can be used on all large format copiers and laser printers using standard paper. The coating has been adapted to suit xerographic toners which ensures permanent toner adherence. FOLAREX HXF is recommended for use wherever the subsequent copy is subject to extreme requirements. The coating is insensitive to water (test 1 h. at 90°C) and all organic solvents. The copy lies extremely flat and will accept water soluble inks, graphite pens and polymer pencils.

Formats			
Art.Number	Nominal thickness (mm)	Format	Packing quantity
18334.090.44000	0.090	A4	100
18334.090.43000	0.090	А3	100
18334.115.44000	0.115	A4	100
18334.115.43000	0.115	A3	100

Technical data

Characteristic

- Excellent runnability
- Good flatness
- · Excellent toner bonding
- · Heat resistant
- High visual contrast

Finish

• Matt Translucent Surface

Specifications

Nominal thickness (mil)	4.6	
Nominal thickness (mm)	0.115	
Coating Printside	Technical Bureau	
Width (inch)	11.69	



Width (mm)	297
Printside	Identical coating
Format	A3
Length (inch)	16.54
Length (mm)	420
Base Material	Polyester film
Packing quantity	100

Compatibility

Handling

- For correct feeding please follow the equipment suppliers manual.
- Avoid moisture and fingerprints.

Storage

- Once packaging is opened, store at a room temperature of 15 25°C and at a humidity of 30 60 %
- Store in a cool and dry place

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.





