

DATA SHEET 20730.180.32200

## Folajet CL UV

Clear transparent polyester film for window graphics, photographic overlays, industrial graphics, nameplates and switch panels. The film is tear resistant and has excellent transparency properties for good see through clarity. It offers superior ink adhesion, water and wet smear resistance as well as good light stability. The film is ideally suited for demanding applications where ink adhesion on flexible surfaces is an important factor.

### Printing Systems



### Rolls

Art.Number	Width (mm)	Length (m)	Nominal thickness (mm)
20730.180.32200	1270	30	0.180

### Technical data

#### Characteristic

- Brilliant, true colour reproduction with or without back lighting
- Can be used in front and back print mode (right reading resp. mirror prints)
- Good ink absorption
- Good ink adhesion
- Light-fast and wet smear resistant prints
- UV curing
- Improved water resistance

#### Finish

- Clear transparent

## Specifications

Coating Printsideside	Ink Jet
Width (inch)	50
Width (mm)	1270
Printsideside	Slightly matted, rougher side
Length (ft)	98.43
Length (m)	30
Nominal thickness (mil)	7.2
Nominal thickness (mm)	0.180
Base Material	Polyester
Packing quantity	1

## Compatibility

- Useable on most large format Ink Jet printers using UV curing ink systems.
- Not recommended for printing with oil, solvent or water based inks.

## Handling

- Between 15-30°C and 30-70% r.h.
- A preconditioning period of 24 hours within the printing environment is recommended.
- Lamination: cold or heat laminates (low-temp) possible but not necessarily essential.
- Only print on the Ink Jet coated side
- Avoid fingerprints on printing side.

## Storage

- Unopened in original packaging storage time is 1 year after shipment (under recommended storage conditions).
- Store in a cool and dry place at a room temperature of 15 - 25°C and at a humidity of 30 - 60%.

### Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.

