

DATA SHEET 14PF2.210.36000

REGUsign PF2

A varnish still represents the most durable option to apply lettering in sign making. On difficult, uneven surfaces it often is the only option. Ever since the self-adhesive cutting stencil, masking tape by Regulus has been known for its qualities: It provides razor-sharp edges, will remain puncture-proof even if several layers are applied, and can be removed without leaving any residue, all of which allows you to work professionally with tarp, vehicles, facades, and awnings. In addition, paper stencils offer a significant benefit when compared to film: They are friendlier to the environment.

Rolls

Art.Number	Width (mm)	Length (m)
14PF2.210.32100	1200	25
14PF2.210.36000	600	25

Technical data

Characteristic

Application:

Paint masks, cut by plotters or manually, for solvent based or water based laquers, for use on uneven or rough surfaces like: Plastered walls (indoor and outdoor), concrete, wood, textiles, awnings, special paint and other surfaces where REGUpac RCS or REGUsign P20 cannot be used. Individual tests are always required in advance.

Properties:

- High precision edges
- Simple weeding of small and large characters
- Perfect adhesion on the above mentioned surfaces
- No curl of the open edges with aqueous or solvent based laquers
- Precise edges even after long drying time

- Multiple layers of paint possible
- Can be removed without residues if applied on an appropriate surface

Finish

Special stencil paper for paint masks on difficult surfaces, with optimised adhesive, with siliconized release liner.

Specifications

Release liner	siliconized paper
Width (mm)	600
Core Diameter	76 mm
Adhesion strength	~ 3.5 - 5.0 N / 25 mm (A.F.E.R.A)
Type of adhesive	natural caoutchouc
Length (m)	25
Base Material	coated special paper
Total thickness	220my +/-20%, 195g/m ² +/-15%
Packing quantity	1 roll

Handling

Preparation:

The surfaces must be dry and free of dust, grease, silicone or other impurities which could influence the adhesion of the mask or the paint.

Temperatures:

The temperature during the application must reach at least 15°C.

Cutting:

The best pressure of the knife is reached, if fine details are easy to weed and the release liner is not cut.

Weeding:

The positive parts of the mask are removed with tweezers, a needle, a knife or any other suitable tool.

Mounting:

A medium or high tack application tape (film or paper) should be used for mounting.

Laquering:

With a brush or a roller or by air brush, in multiple layers if required.

To achieve a good painting it is important to work thoroughly and to choose the right degree of dilution of the paint as well as a paint thinner adapted for the application. For this reason the recommendations of the paint manufacturer must be observed imperatively.

Removing:

The paint mask can only be removed after sufficient drying of the paint.

Special hints for lettering of façades:

Lettering only on fully dried paint at temperatures of 15°C minimum.

The adhesion of the stencil might be more difficult on paints, which are repelling dirt and water, as their ingredients might as well repel the adhesive of REGUsign PF2.

Please use low tack application tape for mounting the stencil on very rough or structured plaster. This ensures the easy removal of the application tape after mounting.

The edges of the stencil should be pushed against the surface using a brush. In order to avoid colours running under the edges, do not brush or roll the paint but knock a small quantity of colour in using a hard brush. To reduce a possible running of the colour in case of application on very structured surfaces, the edges of the stencil should be additionally lacquered with a ground colour.

Storage

- Store in a cool and dry place

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.