

DATA SHEET 21135.320.38800

## Folajet Canvas P

A matt top coated true canvas fabric cloth for high resolution Giclee fine art prints, classic paintings and photographs to create that traditional classic textured canvas. The coated front and the back surface are matched to a classic fine art canvas. Special inkjet coating for printing with pigment inks as well as dye inks.

### Printing Systems



### Rolls

Art.Number	Width (mm)	Grammage	Length (m)
21135.320.35700	610	320 g/m <sup>2</sup>	10
21135.320.38800	914	320 g/m <sup>2</sup>	10
21135.320.31800	1270	320 g/m <sup>2</sup>	10

### Technical data

#### Characteristic

- High brilliance of colours
- Neutral Colour image reproduction
- Suitable for dye inks
- Suitable for Latex printers
- Suitable for piezo Ink Jet printer
- Suitable for pigment inks which offers improved light stability
- Suitable for thermal Ink Jet printer
- Good ink absorption
- Excellent outstanding durability of the prints
- Excellent outstanding durability of the prints when using pigmented inks
- Instant dry
- Improved water resistance

## Finish

- Brownback
- Natural, matt

## Specifications

Basic weight (g)	320
Basic weight (oz)	11.29
Coating Printsides	For Ink Jet
Width (inch)	36
Width (mm)	914
Printside	Natural, matt
Length (ft)	32.81
Length (m)	10
Backside	Brown side
Base Material	Polycotton, 1:1 weave
Packing quantity	1 roll

## Compatibility

### Handling

- Switch off automatic cutting device (damage to print heads and cutting knives).
- Between 15-30°C and 30-70% r.h.
- Please observe the specifications for your printer and the RIP software.
- Printer mode: fine art paper, mat coated paper o.s.
- Print side = matt white side
- A preconditioning period of 24 hours within the printing environment is recommended.
- Ink Load: approx. 260 - 300% (may vary according to ink system and RIP calibration).
- Avoid fingerprints on printing side.

### Storage

- Shelf life: 1 year after delivery
- Store in the closed original packaging in a cool and dry place at a room temperature of 15 - 25°C and at a humidity of 30 - 60%.

### Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the

complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.