

DATA SHEET 03508.310.38900

Fine Art Paper Contour

A top coated matt archival artist paper with a subtle texture which is made from 100% cellulose, for producing high quality fine art reproductions or fine art photography. The coating ensures stunningly brilliant colours with superb flatness with high density blacks. Ideal for classic paintings.

Printing Systems



Rolls

Art.Number	Basic weight (g)	Width (mm)	Length (m)
03508.310.33900	310	431	15
03508.310.35800	310	610	15
03508.310.38900	310	914	15
03508.310.30900	310	1118	15
03508.310.31900	310	1270	15

Technical data

Characteristic

- Neutral Colour image reproduction
- Very finely defined prints
- Suitable for dye inks
- Suitable for Latex printers
- Suitable for piezo Ink Jet printer
- Suitable for pigment inks which offers improved light stability
- Suitable for thermal Ink Jet printer
- Good ink absorption
- Excellent outstanding durability of the prints when using pigmented inks
- Matt white fine art paper, acid-free, on 100% cellulose base
- Excellent outstanding durability of the prints when using pigmented inks

- Saturated black and white and colour prints
- Instant dry

Finish

- White matt, smooth structured surface

Specifications

Basic weight (g)	310
Basic weight (oz)	10.94
Coating Printsides	Ink Jet
Width (inch)	36
Width (mm)	914
Printside	Slightly tacky side
Length (ft)	49.22
Length (m)	15
Nominal thickness (mil)	18.4
Nominal thickness (mm)	0.460
Base Material	Fine Art Paper
Packing quantity	1

Compatibility

- Suitable for most Ink Jet plotters using dye- or pigmented inks
- Not compatible with oil and solvent based systems.

Handling

- Switch off automatic cutting device (damage to print heads and cutting knives).
- Between 15-30°C and 30-70% r.h.
- Please observe the specifications for your printer and the RIP software.
- Printer mode: fine art paper, mat coated paper o.s.
- A preconditioning period of 24 hours within the printing environment is recommended.
- Ink Load: approx. 260 - 300% (may vary according to ink system and RIP calibration).
- Only print on the Ink Jet coated side
- The end of the paper roll is attached to the core with double sided tape. Please monitor carefully the final part of this paper.
- Avoid fingerprints on printing side.

Storage

- Unopened in original packaging storage time is 1 year after shipment (under recommended storage conditions).

- Store in the closed original packaging in a cool and dry place at a room temperature of 15 - 25°C and at a humidity of 30 - 60%.

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.