

DATA SHEET 06657.180.84500

## Folex Digiprint-IG/WODS

Digital printing on durable substrates such as Folex Digiprint IG coated polyester films are an excellent and effective choice for a variety of applications. Digiprint IG/WODS can be printed on front and back side.

### Formats

Art.Number	Width (mm)	Format	Length (mm)	Nominal thickness (mm)	Packing quantity
06657.180.84500	320	SRA3	450	0.180	200
06658.250.84500	320	SRA3	450	0.250	200
06657.180.87400	530		750	0.180	100
06658.250.87400	530		750	0.250	100

### Technical data

#### Characteristic



- Superb ink adhesion and image transfer
- Duplex printing possible
- Easy storage
- Excellent dimensional stability
- Suitable for short and long runs
- Suitable for Clean Room applications
- Tear resistant
- Consistent performance
- Dedicated coating for Indigo Electro Ink
- No limited shelf life
- Splash resistant

#### Finish

- White glossy

## Specifications

Coating Printsideside	HP Indigo Electro Ink
Width (inch)	12.6
Width (mm)	320
Printside	Special reactive coating for toner, printable both sides
Format	SRA3
Length (inch)	17.72
Length (mm)	450
Nominal thickness (mil)	7.2
Nominal thickness (mm)	0.180
Base Material	Polyester film
Packing quantity	200

## Compatibility

- Suitable for Digital Presses from HP Indigo
- Not compatible with dry toner Digital Presses. (See Folex Digiprint-XE and -NX series).

## Handling

- A preconditioning period of 24 hours within the printing environment is recommended.
- Please carefully follow the handling instructions supplied with this product as well as the press manufacturers manual.
- No special handling required.
- Avoid fingerprints on printing side.

## Storage

- Shelf life: 1 year after delivery
- Store in the closed original packaging in a cool and dry place at a room temperature of 15 - 25°C and at a humidity of 30 - 60%.

## Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.