

DATA SHEET 06874.090.84500

Folex Digiprint-IG/MAK

Specially coated polyester film for Electro Ink with a Matt translucent surface. The film is heat stabilized for good flatness properties and the coating offers excellent ink transfer & bonding for consistent image performance. Paper backing along the short side for smooth feedability.

Formats

Art.Number	Format	Nominal thickness (mm)	Packing quantity
06874.090.84500	SRA3	0.090	200

Technical data

Characteristic



- Superb ink adhesion and image transfer
- Easy storage
- Excellent dimensional stability
- Suitable for short and long runs
- Tear resistant
- Consistent performance
- Dedicated coating for Indigo Electro Ink
- No limited shelf life
- Splash resistant

Finish

- Paper backed short side
- Translucent matt

Specifications

Coating Printside	HP Indigo Electro Ink
Width (inch)	12.6

Width (mm)	320
Printside	Film side
Format	SRA3
Length (inch)	17.72
Length (mm)	450
Nominal thickness (mil)	3.6
Nominal thickness (mm)	0.090
Backside	Paperbacked short side
Total Thickness (mil)	6.2
Total Thickness (mm)	0.155
Base Material	Polyester film
Packing quantity	200

Compatibility

- Suitable for Digital Presses from HP Indigo
- Not compatible with dry toner Digital Presses. (See Folex Digiprint-XE and -NX series).

Handling

- A preconditioning period of 24 hours within the printing environment is recommended.
- Please carefully follow the handling instructions supplied with this product as well as the press manufacturers manual.
- No special handling required.
- Avoid fingerprints on printing side.

Storage

- Shelf life: 1 year after delivery
- Store in the closed original packaging in a cool and dry place at a room temperature of 15 - 25°C and at a humidity of 30 - 60%.

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.