

DATA SHEET 06905.100.84500

Folex Digiprint-IG/SIK

Specially coated polyester film for Electro Ink with a silver metallic surface. The film is heat stabilized for good flatness properties and the coating offers excellent ink transfer and bonding for consistent image performance.

Formats

| Art.Number | Format | Nominal thickness (mm) | Packing quantity |
|-----------------|--------|------------------------|------------------|
| 06905.100.84500 | SRA3 | 0.100 | 200 |

Technical data

Characteristic



- Superb ink adhesion and image transfer
- Easy storage
- Excellent dimensional stability
- Suitable for short and long runs
- Officially approved by HP Indigo test centre
- Tear resistant
- Consistent performance
- Dedicated coating for Indigo Electro Ink
- No limited shelf life
- Splash resistant

Finish

- Paper backed short side
- Silver metallic glossy

Specifications

| | |
|--------------------|-----------------------|
| Coating Printsides | HP Indigo Electro Ink |
| Width (inch) | 12.6 |

| | |
|-------------------------|------------------------------------|
| Width (mm) | 320 |
| Printside | Special reactive coating for toner |
| Format | SRA3 |
| Length (inch) | 17.72 |
| Length (mm) | 450 |
| Nominal thickness (mil) | 4 |
| Nominal thickness (mm) | 0.100 |
| Backside | Paperbacked short side |
| Total Thickness (mil) | 7.04 |
| Total Thickness (mm) | 0.176 |
| Base Material | Polyester film |
| Packing quantity | 200 |

Compatibility

- Suitable for Digital Presses from HP Indigo
- Not compatible with dry toner Digital Presses. (See Folex Digiprint-XE and -NX series).

Handling

- A preconditioning period of 24 hours within the printing environment is recommended.
- Please carefully follow the handling instructions supplied with this product as well as the press manufacturers manual.
- No special handling required.
- Avoid fingerprints on printing side.

Storage

- Shelf life: 1 year after delivery
- Store in the closed original packaging in a cool and dry place at a room temperature of 15 - 25°C and at a humidity of 30 - 60%.

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.