DATA SHEET 06889.250.86900

Folex Digiprint-IG/CLSC

Specially coated static cling film for Electro Ink with a clear transparent surface. The film is heat stabilized for good flatness properties and the coating offers excellent ink transfer & bonding for consistent image performance. The film has a silicon release liner which is removed when applying to a window type surface.

Formats

Art.Number	Width (mm)	Format	Length (mm)	Nominal thickness (mm)	Packing quantity
06889.250.84400	320	SRA3	450	0.275	100
06889.250.86900	500		700	0.275	100

Technical data

Characteristic

- Back layer clings to smooth surfaces (glass, metall) without adhesives, easy to remove
- Superb ink adhesion and image transfer
- Easy storage
- Excellent dimensional stability
- Suitable for short and long runs
- Officially approved by HP Indigo test centre
- Tear resistant
- Consistent performance
- Dedicated coating for Indigo Electro Ink
- No limited shelf life
- Splash resistant

Finish

- Clear transparent

Specifications

Coating Printside	HP Indigo Electro Ink
Coating Thickness (mil)	0.48
Coating Thickness (mm)	0.010
Width (inch)	19.68
Width (mm)	500
Printside	Special reactive coating for toner, glossy side
Length (inch)	27.56
Length (mm)	700
Nominal thickness (mil)	11
Nominal thickness (mm)	0.275
Backside	PVC Cling layer with thin protection sheet
Total Thickness (mil)	11.48
Total Thickness (mm)	0.287
Base Material	Polyester / PVC Film
Packing quantity	100

Compatibility

- Suitable for Digital Presses from HP Indigo
- Not compatible with dry toner Digital Presses. (See Folex Digiprint-XE and -NX series).

Handling

- A preconditioning period of 24 hours within the printing environment is recommended.
- Please carefully follow the handling instructions supplied with this product as well as the press manufacturers manual.
- No special handling required.
- Avoid fingerprints on printing side.

Storage

- Shelf life: 1 year after delivery
- Store in the closed original packaging in a cool and dry place at a room temperature of 15 - 25°C and at a humidity of 30 - 60%.

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to

our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.