

DATA SHEET 06745.100.75400

Folex Digiprint-XE/MX

Specially coated polyester film with a double matt translucent surface which is suitable for printing on both sides. The film is heat stabilized for good flatness properties and the coating offers excellent toner bonding for image permanence.

Printing Systems



Rolls

Art.Number	Width (mm)	Length (m)	Nominal thickness (mm)
06745.100.75400	0.100	500	500

Technical data

Characteristic



- Duplex printing possible
- Excellent dimensional stability
- Suitable for Clean Room applications
- Excellent toner bonding
- Officially approved by Xeikon - Class 1A
- Tear resistant
- Consistent performance
- Dedicated script files
- Dedicated coating for dry toner digital presses
- No limited shelf life
- Splash resistant

Finish

- Translucent matt

Specifications

Coating Printsides	Xeikon dry toner
Width (inch)	19.69
Width (mm)	500
Printside	Special coating for toner, printable both sides
Length (ft)	1640.5
Length (m)	500
Nominal thickness (mil)	4
Nominal thickness (mm)	0.100
Base Material	Polyester film
Packing quantity	1

Compatibility

- Suitable for Digital Presses from Xeikon and compatible brands.
- Not compatible with liquid toner Digital Presses (see Folex Digiprint -IG series).

Handling

- Please follow the handling instructions supplied with this product as well as the machine manufacturers manual.
- A preconditioning period of 24 hours within the printing environment is recommended.
- No preconditioning within the press required.
- Avoid fingerprints on printing side.

Storage

- Shelf life: 1 year after delivery
- Store in the closed original packaging in a cool and dry place at a room temperature of 15 - 25°C and at a humidity of 30 - 60%.

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.