



Folaproof Laserfilm/F

Text, graphs, halftone and line work designed on a PC or MAC can be transfer directly, dry and without any chemical processing. The special surface gives excellent toner bonding and the high visual contrast enables a quick check of the output image.

Printing Systems





Formats

| Art.Number | Format | Nominal thickness (mm) | Packing quantity |
|-----------------|--------|------------------------|------------------|
| 09734.090.44000 | A4 | 0.090 | 100 |
| 09734.090.43000 | A3 | 0.090 | 100 |
| 09735.115.44000 | A4 | 0.115 | 100 |
| 09735.115.43000 | A3 | 0.115 | 100 |

Technical data

Characteristic

- Excellent runnability
- Good flatness
- Excellent toner bonding
- · Heat resistant
- · High visual contrast

Finish

• Matt Translucent Surface

Specifications

| Coating Printside | Laser & Copier mono |
|-------------------|---------------------|
| Width (inch) | 11.69 |



| Width (mm) | 297 |
|-------------------------|----------------|
| Printside | Identical |
| Format | A3 |
| Length (inch) | 16.54 |
| Length (mm) | 420 |
| Nominal thickness (mil) | 4.6 |
| Nominal thickness (mm) | 0.115 |
| Base Material | Polyester film |
| Packing quantity | 100 |

Compatibility

• For use on most black and white copiers and laser printers.

Handling

- Please follow the handling instructions supplied with this product as well as the Copier / Printer manufacturers manual.
- Avoid moisture and fingerprints.

Storage

- \bullet Once packaging is opened, store at a room temperature of 15 25°C and at a humidity of 30 60 %
- Shelf life 1 year after delivery (under recommended storage conditions)
- Store in a cool and dry place

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.