

DATA SHEET 04807.000.44100

Textrans ST/S

Special coated paper to print your own design onto white or light coloured T-shirts, caps or any other cotton based fabric. After printing, transfer the carrier image onto the fabric with the use of a Transfer Press.

We suggest you do NOT use TEXTRANS ST on Printers / Copiers with extremely high fusing Temperatures (such as Canon CLC / iRC3200 / 3220) We recommend TEXTRANS HT for these very hot machines.

Printing Systems



Formats		
Art.Number	Format	Packing quantity
04807.000.44100	A4	50
04807.000.43100	A3	50

Technical data

Characteristic



Heat-Press activation

Finish

- Feeding Edge Short
- Transfer paper

Specifications

Coating Printside

Laser & Copier colour



PrintsideWhite sideFormatA4Length (inch)11.69Length (mm)297BacksideInterleaving paperBase MaterialTransfer Paper	Width (inch)	8.27
FormatA4Length (inch)11.69Length (mm)297BacksideInterleaving paperBase MaterialTransfer Paper	Width (mm)	210
Length (inch)11.69Length (mm)297BacksideInterleaving paperBase MaterialTransfer Paper	Printside	White side
Length (mm)297BacksideInterleaving paperBase MaterialTransfer Paper	Format	A4
BacksideInterleaving paperBase MaterialTransfer Paper	Length (inch)	11.69
Base Material Transfer Paper	Length (mm)	297
	Backside	Interleaving paper
Packing quantity 50	Base Material	Transfer Paper
	Packing quantity	50

Compatibility

• For use on most Mono & Colour Laser Printers.

Handling

- Please follow the handling instructions supplied with this product as well as the Copier / Printer manufacturers manual.
- Avoid moisture and fingerprints.

Storage

- Once packaging is opened, store at a room temperature of 15 25°C and at a humidity of 30 60%.
- Shelf life: 1 year after delivery
- Store in a cool and dry place

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.