

DATA SHEET 68100.175.32200

LADF 0175

Laser Ablative Dry Film

Formats

Art.Number	Nominal thickness (mm)
68100.175.99999	0.175

Rolls

Art.Number	Width (mm)	Length (m)	Nominal thickness (mm)
68100.175.34600	500	30	0.175
68100.175.37600	762	30	0.175
68100.175.30700	1067	30	0.175
68100.175.32200	1270	30	0.175

Technical data

Specifications

Coating Printsides	Mat, black
Nominal thickness (mm)	0.175
Base Material	PET

Storage

- The LADF (unexposed and exposed) should be stored in a cool, dark and dry environment at 15 - 25 °C / 59 - 77 °F (room temperature) and a relative humidity of approx. 50 - 60 %. Higher temperatures or colder (even for a short period of time) can affect the functionality of the film. If the temperature of the plate making room differs significantly from that of the storage room, the LADF should be adapted to the temperature of the plate making room prior to their use (approx. 15 hours) to get best dimension stability properties.
- Shelf life: 1 year after delivery

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.