

DATA SHEET 12008.150.99900

Folabase Excel U

UNDERPACKING FOIL NON ADHESIVE

Folabase Excel U is an advancement of our proven "Folabase Soft U" in the thickness ranges from 0.7 to 1.5 mm and reliably supports the achievement of outstanding printing results in cylinder circumference and printing length adjustment in offset presses.

We have been able to significantly improve the plane parallelism of the underpacking materials at larger thicknesses, by using a new raw material.

The combination of dimensionally stable polyester and a flexible polymer offers outstanding dimensional stability in thickness and format, as well as a extensive smash resistance.

Compared to paper substrates, the board is largely resistant to swelling caused by dampening water or cleaning agents. It can be reused frequently or used directly over a longer period of time, making it a particularly sustainable option.

Formats

Art.Number	Nominal thickness (inch)	Nominal thickness (mm)
12008.700.99900	.028	0.70
12008.750.99900	.030	0.75
12008.800.99900	.031	0.80
12008.900.99900	.035	0.90
12008.950.99900	.037	0.95
12008.150.99900	.059	1.50

Rolls

Art.Number	Width (inch)	Length (m)	Nominal thickness (inch)	Nominal thickness (mm)
12008.700.11300	1270	50	.028	0.70
12008.750.11300	1270	50	.030	0.75
12008.800.11300	1270	50	.031	0.80

12008.900.11300	1270	50	.035	0.90
12008.950.11300	1270	50	.037	0.95
12008.150.11300	1270	50	.059	1.50

Technical data

Characteristic



- Paper jam-resistant Crease-resistant / self-healing
- Polyester-basis/ -carrier

Finish

- Soft surface

Compatibility

- Paperlike underpacking film

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.