



DATA SHEET 12015.300.99900

Folabase H 48

UNDERPACKING FOIL, SELF-ADHESIVE

Folabase H48 is a new Folex product in the segment of self-adhesive underpacking foils. Corrosion-inhibiting additives in our Folabase H48 underpacking foil protect the cylinder surface. The foil can be easily applied to almost all cylinders and can be removed quickly and cleanly with very little cleaning effort. The foils release film consists of siliconised propylene, this prevents wrinkling and avoids dust inclusion. Given its high resistance to chemical cleaners and solvents, Folabase H48 is characterised by a long service life. The foil demonstrates very good thermal stability on the press.

For product introduction by video please click here.

| Formats | | | |
|-----------------|------------------------|--------------------------|--|
| Art.Number | Nominal thickness (mm) | Nominal thickness (inch) | |
| 12015.080.99900 | 0.08 | .0031 | |
| 12015.100.99900 | 0.10 | .0039 | |
| 12015.120.99900 | 0.12 | .0047 | |
| 12015.140.99900 | 0.14 | .0055 | |
| 12015.160.99900 | 0.16 | .0063 | |
| 12015.180.99900 | 0.18 | .0071 | |
| 12015.200.99900 | 0.20 | .0079 | |
| 12015.220.99900 | 0.22 | .0087 | |
| 12015.240.99900 | 0.24 | .0094 | |
| 12015.260.99900 | 0.26 | .0102 | |
| 12015.280.99900 | 0.28 | .0110 | |
| 12015.300.99900 | 0.30 | .0118 | |
| 12015.320.99900 | 0.32 | .0126 | |
| 12015.350.99900 | 0.35 | .0138 | |
| 12015.400.99900 | 0.40 | .0157 | |
| 12015.450.99900 | 0.45 | .0177 | |
| 12015.500.99900 | 0.50 | .0197 | |



| $\overline{}$ | 11 | |
|---------------|----|--|
| | | |

| Art.Number | Width (mm) | Length (m) | Nominal thickness | Nominal thickness |
|-----------------|------------|------------|-------------------|-------------------|
| | | | (inch) | (mm) |
| 12015.080.31350 | 1270 | 50 | .0031 | 0.08 |
| 12015.100.31350 | 1270 | 50 | .0039 | 0.10 |
| 12015.120.31350 | 1270 | 50 | .0047 | 0.12 |
| 12015.140.31350 | 1270 | 50 | .0055 | 0.14 |
| 12015.160.31350 | 1270 | 50 | .0063 | 0.16 |
| 12015.180.31350 | 1270 | 50 | .0071 | 0.18 |
| 12015.200.31350 | 1270 | 50 | .0079 | 0.20 |
| 12015.220.31350 | 1270 | 50 | .0087 | 0.22 |
| 12015.240.31350 | 1270 | 50 | .0094 | 0.24 |
| 12015.260.31350 | 1270 | 50 | .0102 | 0.26 |
| 12015.280.31350 | 1270 | 50 | .0110 | 0.28 |
| 12015.300.31350 | 1270 | 50 | .0118 | 0.30 |
| 12015.320.31350 | 1270 | 50 | .0126 | 0.32 |
| 12015.350.31350 | 1270 | 50 | .0138 | 0.35 |
| 12015.400.31350 | 1270 | 50 | .0157 | 0.40 |
| 12015.450.31350 | 1270 | 50 | .0177 | 0.45 |
| 12015.500.31350 | 1270 | 50 | .0197 | 0.50 |


Technical data

Characteristic









- Polyester-basis/ -carrier
- Repositionable

Specifications

| Nominal thickness (mm) | 0.30 |
|--------------------------|-------|
| Nominal thickness (inch) | .0118 |





Compatibility

- For a hard substrate packing.
- For Plate Cylinder

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.