

DATA SHEET 12920.028.28001

ROTOCALCO® Grinding stones for steel surfaces

Steel material needs to be removed evenly at the cylinder base in order to create a suitable substrate for later copper plating. Rotocalco steel grinding stones are designed to aggressively remove stock without generating undesirable grinding patterns. This product is available in a 280 grit for more aggressive grinding, and a 400 grit for more polished finishing.

Formats

Art.Number	Grit size	Outer Hole Diameter in mm	Height approx. (mm)	Centre Hole Diameter in mm	pcs per package
12920.028.28001	280	190	50	50	14
12920.040.40001	400	190	50	50	14

Technical data

Specifications

Grit size	280
Outer Hole Diameter in mm	190
Height approx. (mm)	50
Centre Hole Diameter in mm	50
pcs per package	14

Compatibility

- Grindstones for chrome surfaces
- Grinding stones for steel surfaces

Handling

Outside diameter of grinding stone +/- 5 mm

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.