

DATA SHEET 07056.130.99900

Folanorm Montage Film SF-AS

Polyester Montagefilm with anti-static surface treatment for screenprint and offsetprint-montage.

Formats

Art.Number	Nominal thickness (mm)	Packing quantity
07055.100.99900	0.100	100
07056.130.99900	0.130	100
07057.180.99900	0.180	100

Rolls

Art.Number	Length (m)	Nominal thickness (mm)
07055.100.19900	50	0.100
07056.130.19900	50	0.130
07057.180.19900	50	0.180

Technical data

Finish

- Clear transparent

Specifications

Nominal thickness (mm)	0.130
Base Material	Polyester film
Packing quantity	100

Compatibility

- Suitable for offset montages

Storage

- Once packaging is opened, store at a room temperature of 15 - 25°C and at a humidity of 30 - 60 %
- Store in a cool and dry place

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.